IN THE CLAIMS:

The claims are listed as follows:

- 1. (Original) Reinforcement ply for a tire, formed of reinforcement elements embedded in coating products, wherein it comprises a first and a second layer of metallic elements parallel to one another, embedded in a coating product or coating products and, between the said two layers, a third layer of elements made from a textile material and embedded in a coating product, the said textile elements being orientated relative to the metallic elements of the said two layers at an angle between 70° and 110°.
- 2. (Original) Reinforcement ply according to Claim 1 wherein the textile material is aromatic polyamide.
- 3. (Original) Ply according to Claim 1, wherein the textile elements are monofilaments.
- 4. (Original) Ply according to Claim 1, wherein the metallic elements are steel cables said to be elastic and are identical in the first and second layers.
- 5. (Original) Ply according to Claim 4, wherein the rubber mixtures of the three layers have identical constitution.

Attorney's Docket No. <u>033818-017</u> Application No. <u>Unassigned</u>

Page 4

6. (Original) Ply according to Claim 4, wherein the mixtures of the said two layers have

identical constitution while the mixture of the third layer has a different constitution.

7. (Currently Amended) Tire with a radial carcass reinforcement surmounted radially by

a crown reinforcement comprising at least one so-termed protection ply, wherein the said

ply is a ply according to any of Claims 1 to 6 Claim 1.